

PRODUCT OVERVIEW

Euro Poplar *Populus spp.* is a high grade interior ply with excellent edge detail. Poplar is widely used for its weight saving features in fit-outs for mobile homes, boats and caravans. The lightest colour in Plymasters' range of plywoods, this product is manufactured from 100% renewable, plantation-grown timber. (The option of using with HPL laminates is available.)

USES

- ♦ Motor-home and Caravan Fit-outs
- ♦ Light Coloured Wall Linings
- ♦ Tiny-house Interiors and Horse Float Interiors
- ♦ Lightweight Cabinetry
- ♦ Feature Joinery Cabinetry



Light but stable, Euro Poplar is a favourite with joiners. Left: Stylish retail display shelves. Above: Edge detail, 18mm Euro Poplar.

SPECIFICATIONS

Sheet Size	Sheet Thickness	Weight	Grading
2440x1220	3mm	3.5kg	BB Interior
2440x1220	6mm	6.5kg	BB Interior
2440x1220	9mm	11.4kg	BB Interior
2440x1220	12mm	15.3kg	BB Interior
2440x1220	18mm	21.5kg	BB Interior
2440x1220	25mm	21.5kg	BB Interior

Colour	White
Durability	Good durability/Interior
Origin	Southern Europe
Environmental	Sustainable

SPECIFICATIONS

Code	Size	Thickness	Info	Grade
EI003	2440 x 1220	3mm	3.3Kg	BB Interior
EI006	2440 x 1220	6mm	6.5Kg	BB Interior
EI009	2440 x 1220	9mm	11.4Kg	BB Interior
EI012	2440 x 1220	12mm	15.3Kg	BB Interior
EI015	2440 x 1220	15mm	18.4Kg	BB Interior
EI018	2440 x 1220	18mm	21.5Kg	BB Interior
EI025	2440 x 1220	25mm	30Kg	BB Interior

HANDLING & APPLICATION INFORMATION

Euro Poplar ply is a softer timber than other plywoods but does harden once a good quality lacquer is applied. Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.