



Plymasters

# Plymasters

## Building Product Information Sheet

Designated building product: Class 1

### Product

|            |  |
|------------|--|
| Name       | Flooring Pine CD F11 Structural T&G              |
| Identifier | Flooring Pine CD F11 Structural T&G - UT or H3.2 |

### Description

T&G flooring construction pine is perfect for residential, commercial and industrial projects. Renowned for its strength, ease-of-use, and reliability: it won't let you down. Available treated to H3.2 (CCA treated) and also in untreated to be used in areas where contact with moisture is not a consideration. With plastic tongue and groove for easy interlocking.

### Technical Specs

|                     |   |
|---------------------|---|
| Available Sizes     | 2400 x 1200   |
| Available Thickness | 19mm  |
| Colour              | Creamy yellow to light brown with green treatment colouring |
| Core                | Pine - Radiate Ply+ Plastic T&G                             |
| Glue Bond           | Super E0 (A Bond)   |

Treatment: Untreated or H3.2 Treated

### Uses

- Flooring
- Wall Linings
- DIY Projects
- General Construction

### Limitations of Use

Not for use in fire surrounding applications.

Untreated is Not for exposed external use. Not to be used in areas directly exposed to water.

H3.2 Treated can be used for external applications and can be directly exposed to water. However should not be in areas directly exposed to water for long periods of time eg. Pool

**Handling & Application /** Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse, we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.



Plymasters

0800 344 112

plymasters.co.nz

281 Heads Road, Castlecliff, Whanagnui 4501



Plymasters

# Plymasters

## Building Product Information Sheet

Designated building product: Class 1

### Importing Details

|   |                                  |
|---|----------------------------------|
| Place of Manufacture                            | New Zealand                      |
| Legal/ Trading Name of the Manufacturer         | International Panel and Lumber   |
| Address of Manufacturer                         | 3 Trickies Road, Greymouth, 7805 |
| Manufacturer Website                            | www.iplply.nz                    |
| Manufacturer Email                              | sales@iplply.nz                  |
| Manufacturer Phone Number                       | 037 626 759                      |
| Manufacturer New Zealand Business Number (NZBN) | 942903919582                     |

### Contributions to Compliance

- B2 Durability B2.3.1 (c)
- F2 Hazardous Building Materials  
F2.3.1
- B2/AS1 table 1
- Certified to AS/NZ2269
- H3.2 Treated Glue :  
Exterior Conditions Class 3 [EN636-3]
- Untreated glue:  
Dry Conditions - Class 1 [EN636-1]

### Supporting Documentation

For further information, please refer to our website and spec sheet.

<https://plymasters.co.nz/categories/products/transport-construction/flooring-pine-cd-f11-structural-t-and-g?categories%5B1%5D=4>



**Plymasters**

0800 344 112

plymasters.co.nz

281 Heads Road, Castlecliff, Whanagnui 4501