

Plymasters

Caravan Plywood

Thin, lightweight plywood with a white melamine finish, 1F.

Caravan Plywood

White Melamine on Lightweight Plywood.

Key Features:

Core
Plywood Core

Surface
Suede Feel White Melamine

Weight
Light Weight

Durability
HPL Laminate- Anti -scratch

Maintenance
Easy Clean

Face
1F

Code	Sheet Size	Thickness	Colour	Weight	Grading	Finish
E1003-P50	2440 x 1220	3mm	White	4.5kg	1F	Suede Feel Matte

Scope of Use:

- Motorhome & Caravan Interiors
- Residential Commercial Cabinetry
- Commercial Automotive Joinery
- Cabinet Backing

Finish:

Caravan Plywood

White Melamine on Lightweight Plywood.

Technical Specs

Texture	White Matte
Core	Plywood core
Origin	New Zealand
Certification	HPL laminate is BS EN 438-3 approved

Limitations of use

Caravan Plywood is not suitable for use in exterior applications or interior projects where the moisture content would be higher than normal (for e.g. a indoor pool or sauna). While this panel is water resistant, it isn't completely waterproof. Care should be taken to avoid excessive exposure to water, steam, or extreme humidity. Care should also be taken to protect panels from high temperatures caused by steam or heat leaks.

- May not be used as structural elements in walls and ceilings
- Final application must be in interior conditions
- Must not be exposed to excess moisture or humidity

Handling

Plywoodwood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. Store panels in dry, well ventilated conditions, placed horizontally on a flat surface. Avoid over-stacking and keep away from flames or excess heat. Do not store panels in an upright position as this may cause warping.

At Plywoodmasters, precautions are taken to minimise this effect. However, once the plywoodwood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

Our products can be found on:

masterspec EBOSS ARCHIPRO Plymasters.co.nz

Caravan Plywood

White Melamine on Lightweight Plywood.

Maintenance

Caravan Plywood is low maintenance, cost effective and easy to clean. Clean panels with a warm damp cloth (microfibre is ideal), with all excess water removed. Wipe away any remaining moisture with a dry cloth. Alternatively, use a dry cloth with a streak-free glass cleaner or standard household surface cleaning spray. For more difficult stains, try dishwashing detergent on a damp cloth.

Never use the following products on Caravan Plywood as these will damage the surface:
- Abrasive cleaners
- Bleach such as Janola or similar
- Scouring pads, wire wool, sandpaper
- Solvents and thinners.

Colour Consistency

Caravan Plywood has a consistent laminate surface. However there may be very slight differences in laminate colour between factory batches.

Exposure to sunlight and water

Caravan Plywood may fade if exposed to direct UV light over a long period of time. Caravan Plywood may be used in areas with moisture but the edges must be sealed.

Fixing

Fixing options for ceiling and wall linings include glue and pin, construction adhesive (glue), hidden fixing systems and more. Please refer to our Soudal glue fixing guides on our website resources page for glue fixing recommendations with and without metal fixings (pins).







Plymasters

Capital
Kitchens
and Interiors