

Plymasters

Euro Gripdeck

Premium wire mesh anti-slip plywood with a phenolic coating on a durable Euro Birch core.

Euro Gripdeck

Wire-mesh, anti-slip, phenolic coating on a Euro Birch core.

Key Features:

Core
Euro Birch Core

Face
Brown
Wire-mesh

Use
Exterior

Durability
Hard Wearing
Strong core

Life Expectancy
5+ years

Size
2440 wide -
3650 wide
available

Euro Gripdeck Product Info

Code	Sheet Size	Thickness	Weight	Info	Grade
F1030	2440 x 1220	12mm	23.6Kg	220/Lge Wire	Anti-slip/smooth
F1036	2440 x 1220	15mm	29.5Kg	220/Lge Wire	Anti-slip/smooth
F1041-K	2440 x 1220	18mm	35.4Kg	220/Lge Wire	Anti-slip/smooth
F1046	2440 x 1220	21mm	41.3Kg	220/Lge Wire	Anti-slip/smooth

Euro Gripdeck 1500+

Code	Sheet Size	Thickness	Weight	Info	Grade
F1031	2440 x 1525	12mm	29.5 Kg	220/Wire Mesh	Anti-slip/smooth
F1038	2440 x 1525	15mm	36.8 Kg	220/Wire Mesh	Anti-slip/smooth
F1042-K	2440 x 1525	18mm	44.2 Kg	220/Wire Mesh	Anti-slip/smooth
F1047	2500 x 1500	21mm	51.5 Kg	220/Wire Mesh	Anti-slip/smooth
F1032-K	3050 x 1525	12mm	36.8 Kg	220/Wire Mesh	Anti-slip/smooth
F1037	3050 x 1525	15mm	46.1 Kg	220/Wire Mesh	Anti-slip/smooth
F1043	3050 x 1525	18mm	55.3 Kg	220/Wire Mesh	Anti-slip/smooth

Scope of Use:

- Transport and ute decks
- Scaffolding
- Ramps
- Walkway
- Exterior Stair treads

Face:



Euro Gripdeck

Wire-mesh, anti-slip, phenolic coating on a Euro Birch core.

Euro Gripdeck 1850+

Code	Sheet Size	Thickness	Weight	Info	Grade
FI036-L	2440 x 1850	12mm	35.7 Kg	220/Wire Mesh	Anti-slip/smooth
FI037-L-K	2440 x 1850	15mm	44.7 Kg	220/Wire Mesh	Anti-slip/smooth
F1041-L-K	2440 x 1850	18mm	53.6 Kg	220/Wire Mesh	Anti-slip/smooth
F1046-L	2440 x 1850	21mm	62.6 Kg	220/Wire Mesh	Anti-slip/smooth
F1046-L-K	2440 x 1850	21mm	62.6 Kg	220/Wire Mesh	Anti-slip/smooth
F1045-K	3650 x 2000	18mm	86.7 Kg	220/Wire Mesh	Anti-slip/smooth
F1050	3050 x 2000	18mm	75 Kg	220/Wire Mesh	Anti-slip/smooth
F1049	3650 x 2000	21mm	101.2Kg	220/Wire Mesh	Anti-slip/smooth

Euro Gripdeck 1850+

Code	Sheet Size	Thickness	Weight	Info	Grade
F1032-A-K	3050 x 1850	12mm	44.7Kg	220/Wire Mesh	Anti-slip/smooth
F1032-S	3650 x 1850	12mm	53.5Kg	220/Wire Mesh	Anti-slip/smooth
F1043-A-K	3050 x 1850	18mm	67.0Kg	220/Wire Mesh	Anti-slip/smooth
F1043-S-K	3650 x 1850	18mm	80.3Kg	220/Wire Mesh	Anti-slip/smooth
F1045-K	3650 x 2000	18mm	86.7 Kg	220/Wire Mesh	Anti-slip/smooth
F1049	3650 x 2000	21mm	101.2Kg	220/Wire Mesh	Anti-slip/smooth

Euro Gripdeck 1828

Code	Sheet Size	Thickness	Weight	Info	Grade
FI041-Raz20	1800 x 1828	18mm	39.64Kg	220/Wire Mesh	Anti-slip/smooth
FI046-Raz21	2440 x 1828	21mm	62.6Kg	220/Wire Mesh	Anti-slip/smooth
FI046-Raz21	1845 x 1828	21mm	48.39Kg	220/Wire Mesh	Anti-slip/smooth
FI046-Raz31	2095 x 1828	21mm	54.95Kg	220/Wire Mesh	Anti-slip/smooth
FI046-Raz20	1800 x 1828	21mm	47.21Kg	220/Wire Mesh	Anti-slip/smooth
FI046-Raz30	2050 x 1828	21mm	53.77Kg	220/Wire Mesh	Anti-slip/smooth

Euro Gripdeck


Wire-mesh, anti-slip, phenolic coating on a Euro Birch core.

Technical Specs

Core	European Birch Multiply
Overlay	Phenolic Film 220/120g/m2, Wire Mesh Pattern
Glue Bond/ Certification	WBP EN314-2 Class3, Phenolic Resin Adhesive
Formaldehyde	Below Class 1 (<3.5mg)

Limitations of use

While Euro Gripdeck can be used in exterior applications it cannot be used in areas permanently exposed to water such as pools. See the Plymasters website resources page for warrantee.




Premium Euro Gripdeck

This is our top-of-the-range anti-slip board. European-made in Finland from certified Euro Birch, with a hard-wearing dark-brown wire-mesh face that grips even when wet. It's the one engineers across New Zealand reach for when a ute deck, trailer or vehicle fit-out needs to look good and last for years.

Genuine European birch panel built to European standards, it's flatter, tougher and longer-lasting than the alternatives. Reach for Euro whenever the job is outdoors and quality and long service life matter most.

Core European Birch
Origin Finland
Face Dark brown, Wire Mesh
Use Exterior
Thickness 12, 15, 18, 21mm
Sizing Up to 3650 x 2000 mm
Expected Life 5+ Years (Warranty 3 years)




Value Trade Gripdeck

Trade is the smart-budget choice. The same wire-mesh anti-slip face and the same everyday performance as the rest of the range, at a lower price.

It's built on a eucalyptus core with a durable brown phenolic surface, and it handles both exterior and interior work: transport and ute decks, scaffolding, ramps and walkways.

Core Eucalyptus
Origin China
Face Brown, Wire Mesh
Use Exterior/ Interior
Thickness 12, 18mm
Sizing 2440x1220 3050x1525mm
Expected Life 2+ Years



Interior Specialist Hexa-Interior Gripdeck

Hexa-Interior is the board for indoor jobs. It has a birch/eucalyptus core and a durable dark-brown hexagon-pattern face, and it's certified for internal, non-structural use with low formaldehyde, so it's ideal where the work is inside and air quality matters.

Think interior transport flooring and vehicle fit-outs: van floors and drawers, shop-fitting, interior walkways and freight boxes.

Core Birch / Eucalyptus
Origin China
Face Dark brown, Hexagon
Use Interior
Thickness 12, 18mm
Sizing 2440x1220 3050x1525mm
Expected Life 5+ Years (Internal use)

Euro Gripdeck

Wire-mesh, anti-slip, phenolic coating on a Euro Birch core.

Application

Euro Gripdeck anti-slip is made for interior and exterior applications, however an exterior grade sealant must be used on all cut edges and around any screws and holes to ensure water resistance and product longevity.

Handling

Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimise this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

Sealing and Coating Recommendations

To ensure water tightness and longevity please seal all cut edges and any screw and nail holes.

Preparation for Cutting

Please inspect the Euro Gripdeck Panel for defects before cutting. We cannot replace altered sheets.

Fixing

Exterior grade screws are required for exterior use.

* Please refer to the Plymasters website for Warrantee details.

Our products can be found on:

masterspec EBOSS ARCHIPRO Plymasters.co.nz

Certifications / Performance Attributes

E1









Plymasters