

Plymasters

Euro Poplar

Euro Poplar is a light-weight interior grade plywood that is manufactured from plantation-grown European logs.

Euro Poplar

100% Euro Poplar Plywood

Key Features:

Core
Euro Poplar

Veneer Cut
Rotary Cut

Lightweight
Lightweight Poplar

Environmental
Renewable Resource

Edge
Nice edge detail

Colour
Creamy Yellow/Blonde

Code	Size	Thickness	Layup	Weight	Grading
E1009	2500 x 1220	9mm	5Ply	11.4Kg	BB
E1012	2500 x 1220	12mm	7Ply	15.3Kg	BB
E1015	2500 x 1220	15mm	7Ply	18.4Kg	BB
E1018	2500 x 1220	18mm	9Ply	21.5Kg	BB
E1025	2500 X 1220	25mm	11Ply	30kg	BB

Scope of Use:

- Kitchen & Bathroom Cabinetry
- Joinery
- Wall & Ceiling Linings
- Commercial Fit outs

Euro Poplar Veneer:



Euro Poplar

100% Euro Poplar Plywood

Technical Specs

Colour	White
Durability	Good durability / interior
Material	Excellent lightweight & matching properties
Origin	Spain
Environmental	Sustainable - FSC C116880
Emissions	Class E1, as per EN 717-2

Limitations of use

Interior use only.

Our products can be found on:

masterspec EBOSS ARCHIPRO Plymasters.co.nz

Certifications / Performance Attributes

FSC www.fsc.org FSC®C223271 Ask for our FSC-certified products

E1

Euro Poplar

100% Euro Poplar Plywood

Application

Euro Poplar has a good edge grain and fine, rotary cut gain pattern. Applying a sealant, lacquer or stain is necessary to prevent water and moisture damage.

Handling

Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimise this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

Colour Consistency

Euro Poplar is a natural product and will have variation in grain pattern and colour. Please check your sheets before starting your project.

Exposure to sunlight and water

As a natural product, Euro Poplar may fade slightly over time, this a natural effect of plywood a UV protective clear coat may help prevent some fading. All plywood must be properly sealed to prevent swelling and mould from moisture.

Euro Poplar

100% Euro Poplar Plywood

Sealing and Coating Recommendations

To ensure water tightness and longevity please seal both sides and edges of your plywood. We suggest a clear, water-based sealer or lacquer. Oil based sealants may have an effect on the colour of lighter plywoods like pine.

Preparation for Coating

Please inspect plywood for defects before cutting or coating. We cannot replace altered sheets.

Lightly sanding the plywood before coating will help ensure a smooth finish. To prepare for coating, the plywood must be completely clean, dried and free of debris oil, grease and wax.

Fixing

There are a range of fixing types available for plywood depending on the application. We suggest timber screws for cabinetry, joinery and furniture applications.

Fixing options for ceiling and wall linings include glue and pin, construction adhesive (glue), hidden fixing systems and more. Please refer to our Soudal glue fixing guides on the resources page on our website for glue fixing recommendations with and without metal fixings (pins).







Euro Poplar
First Light Studio



Plymasters

