



# Flooring Pine CD F11 Structural T&G

## Specification Sheet

T&G flooring construction pine is perfect for residential, commercial and industrial projects. Renowned for its strength, ease-of-use, and reliability: it won't let you down. Available treated to H3.2 (CCA treated) and also in untreated to be used in areas where contact with moisture is not a consideration. With plastic tongue and groove for easy interlocking.

## Product Info

Code	Sheet Size	Thickness	Treatment	Weight	Grading
P1085-FTG	2400 x1200	19mm	Untreated (UT)	27.3 kg	CD
T1040-FTG	2400 x1200	19mm	H3.2	27.3 kg	CD

## Technical Specs

Available Sizes	2400 x 1200
Available Thickness	19mm
Colour	Creamy yellow to light brown with green treatment colouring (H3.2)
Core	Pine - Radiate Ply+ Plastic T&G
Glue Bond	Super E0 (A Bond)

## Ideal Uses

- Flooring
- Wall Linings
- Bracing
- General Construction

**Handling & Application** / Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse, we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

