

Plymasters

Gaboon MLH

Carcass grade Gaboon plywood with a mixed hardwood core. It has an attractive light pink, almost neutral colour, with a consistent grain.

Gaboon MLH

Carcass Grade Gaboon Plywood with a mixed hardwood core

Key Features:

Core
Mixed Hardwood core

Colour
Light pink - neutral colour

Weight
Lighter weight than other hardwoods

Durability
Hard Wearing

Face Grade
BB

Size
2440 x 1220

Code	Sheet Size	Thickness	Weight	Grading
H1050	2440 x 1220	4mm	7.5kg	BB
H1055	2440 x 1220	6mm	11.5kg	BB
H1060	2440 x 1220	9mm	17kg	BB
H1065	2440 x 1220	12mm	22.5kg	BB
H1075	2440 x 1220	18mm	30.5kg	BB
H1085	2440 x 1220	25mm	46kg	BB

Scope of Use:

- Carcass Cabinetry
- Furniture and Architectural Fit-outs
- Residential Linings

Gaboon MLH:



Gaboon MLH

Carcass Grade Gaboon Plywood with a mixed hardwood core

Technical Specs

Colour	Consistent Light / Med Pink / Neutral Colouring
Origin	South East Asia
Certification	FSC
Emissions	Class E1
Core	Eucalyptus Mixed Hardwood

Limitations of use

Interior use only.

Our products can be found on:

masterspec EBOSS ARCHIPRO Plymasters.co.nz

Certifications / Performance Attributes

FSC E1

Gaboon MLH

Carcass Grade Gaboon Plywood with a mixed hardwood core

Application

Applying a sealant, lacquer or stain is necessary to prevent water and moisture damage.

Handling

Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimise this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

Colour Consistency

Gaboon MLH is a natural product and will have variation in grain pattern and colour. Slight differences in colour in plywood sheets should be expected, please check your sheets before starting your project.

Exposure to sunlight and water

Gaboon MLH may fade if exposed to direct UV light over a long period of time. As a natural product, Gaboon may fade slightly over time, this a natural effect of plywood. All plywood must be properly sealed to prevent swelling and mould from moisture .

Gaboon MLH

Carcass Grade Gaboon Plywood with a mixed hardwood core

Sealing and Coating Recommendations

To ensure water tightness and longevity please seal both sides and edges of your plywood. We suggest solvent-based clear coats or oil finishes for Gaboon as it is a darker timber. This will bring out the grain pattern and natural colour of the plywood.

Preparation for Coating

Please inspect plywood for defects before cutting or coating. We cannot replace altered sheets.

Lightly sanding the plywood before coating will help ensure a smooth finish. To prepare for coating, the plywood must be completely clean, dried and free of debris oil, grease and wax.

Fixing

There are a range of fixing types available for plywood depending on the application. We suggest timber screws for cabinetry, joinery and furniture applications.

Fixing options for ceiling and wall linings include glue and pin, construction adhesive (glue), hidden fixing systems and more. Please refer to our Soudal glue fixing guides on our website resources page for glue fixing recommendations with and without metal fixings (pins).

Maverick Joinery
Gaboon MLH
Wall and ceiling lining









Plymasters