



Classique Eucalyptus

Specification Sheet

The attractive stripe grain pattern makes this decorative interior ply a classic choice for linings and feature walls. The Classique Plywood range is specifically designed for wall and ceiling lining applications. It is a high-grade interior ply with a Euro Poplar core available unfinished or pre-finished. Beautiful and lightweight, this is a decorative interior product that is non-structural.

Product Info

Code	Sheet Size	Thickness	Veneer	Weight	Finish	Grading
V2112-E	2440 x 1220	12mm	Eucalyptus	18kg	Unfinished	AB
V2112-PRE-E	2440 x 1220	12mm	Eucalyptus-Pre	18.5kg	Clear Pre-finished	AB

Technical Specs

Colour	Eucalyptus timber colourings - European Poplar Core
Durability	Good strength/durability
Glue bond	Class 1 (Interior). Density - 440 - 490Kg/m ³
Origin	Spain
Prefinished options	UV Clear finished 2S, 30% gloss, low VOC
Emissions	Class E1 - EN 13986

Ideal Uses

- Ceilings
- Wall Linings
- Feature Ceilings
- Lightweight Cabinetry

Handling & Application / Classique ply is a lighter weight timber than other plywoods, the highly visual surface will harden once a good quality lacquer is applied. Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

