



Classique Eucalyptus

Specification Sheet

The Classique Plywood range is specifically designed for wall and ceiling lining applications. It is a high-grade interior ply with a Euro Poplar core available unfinished or pre-finished. Beautiful and lightweight, this is a decorative interior product that is non-structural.

The unique stripe grain pattern of Eucalyptus Veneers has high variation in shades and colours from dark brown to soft brown and pink resulting in a striking grain pattern which varies in shades and colours from sheet to sheet.

The deviation of colour between faces exist in all natural woods, this is even more accentuated in eucalyptus, which goes through many different brown to pink shades. All timber when UV Coated increase their contrast of grain colours, particularly Eucalyptus, and Oaks.

Product Info

Code	Sheet Size	Thickness	Veneer	Weight	Finish	Grading
V2112-E	2440 x 1220	12mm	Eucalyptus	18kg	Unfinished	AB
V2112-PRE-E	2440 x 1220	12mm	Eucalyptus-Pre	18.5kg	Clear Pre-finished	AB

Technical Specs

Colour	Eucalyptus timber colourings - European Poplar Core
Durability	Good strength/durability
Glue bond	Class 1 (Interior). Density - 440 - 490Kg/m ³
Origin	Spain
Prefinished options	UV Clear finished 2S, 30% gloss, low VOC
Emissions	Class E1 - EN 13986

Installation with Grain Pattern

It is necessary for the installer to select them for placement when used for decorative walls or ceilings (if they want to find some homogeneity in the colour). Select carefully which piece to place next to another, so that the contrasts are not so strong and the change of tone flows in a more natural way. The alternative is to put up randomly which is not uncommon, especially if sheets are installed in less than 2400x1200 sizes.

Our European supplier does not specify CC over against 1/4 Cut (or vice versa) for the Classique range, so this needs to be considered. The sheets of Oaks and Eucalyptus do tend to look like a 1/4 Cut grain.

Ideal Uses

- Ceilings
- Wall Linings
- Feature Ceilings
- Lightweight Cabinetry

Handling & Application / Classique ply is a lighter weight timber than other plywoods, the highly visual surface will harden once a good quality lacquer is applied. Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

