



Rapidline Birch

Specification Sheet

Economy grade Birch on Poplar ply core. Un-finished. Specifically for budget conscious projects. Non-structural CD grade ply.

Product Info

Code	Sheet Size	Thickness	Lay-up	Weight	Grading
J1020-B	2400 x 1200	9mm	3 Ply	13.5kg	CD
J1020-B27	2700 x 1200	9mm	5 Ply	16kg	CD

Technical Specs

Colour	Light Straw/ Creamy coloured timber Grain
Cut	Rotary Cut
Glue bond	MR -Phenolic
Origin	China
Core	Poplar
Environmental	CE & FSC Certified Manufacturer

Ideal Uses

- Wall and Ceiling Linings for Sheds
- Sleep-out Linings
- Bach's & Man Cave Linings
- Lights Commercial Projects

Handling & Application/ Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. At Plymasters, precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important with pine ply (as it is a softwood), where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

