



# Rapidline Birch UV

## Specification Sheet

Economy grade, UV Prefinished Birch on Poplar core ply. Clear low gloss finish - solvent lacquer, UV Cured, thickness around 0.1mm. Veneer and coating can have imperfections. Specifically for budget conscious projects. Non-structural CPD grade ply.

### Product Info

Code	Sheet Size	Thickness	Lay-up	Weight	Grading
J1015-BUV	2400 x 1200	6mm	3 Ply	9.5kg	CD
J1020-BUV	2400 x 1200	9mm	5 Ply	13.5kg	CD
J1025-BUV	2400 x 1200	12mm	7 Ply	18kg	CD
J1020-BUV27	2700 x 1200	9mm	5 Ply	13.5kg	CD

### Technical Specs

Colour	Light Straw/ Creamy coloured timber Grain
Cut	Rotary Cut
Glue bond	MR -Phenolic
Origin	Vietnam / China
Core	Poplar
Environmental	CE Certified Manufacturer
Finish	Low Gloss - Solvent Laquer, UV Cured, thickness around 0.1mm

### Ideal Uses

- Wall and Ceiling Linings for Sheds
- Sleep-out Linings
- Baches & Man Cave Linings
- Lights Commercial Projects

**Handling & Application/** Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. At Plymasters, precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important with pine ply (as it is a softwood), where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

