



Rapidline Birch UV

Specification Sheet

Economy grade, UV Prefinished Birch on Poplar core ply. Clear low gloss finish, veneer and coating can have imperfections. Specifically for budget conscious projects. Non-structural CPD grade ply.

Uses Wall and Ceiling Linings for Sheds, Sleep-outs, Bach's, man-caves & some Light Commercial projects.

Product Info

Code	Sheet Size	Thickness	Lay-up	Weight	Grading
J1015-BUV	2400 x 1200	6mm	3 Ply	9.5kg	CD
J1020-BUV	2400 x 1200	9mm	5 Ply	13.5kg	CD
J1025-BUV	2400 x 1200	12mm	7 Ply	18kg	CD

Technical Specs

Colour	Light Straw/ Creamy coloured timber Grain
Cut	Rotary Cut
Glue bond	MR -Phenolic
Origin	Vietnam / China
Core	Poplar
Environmental	CE & FSC Certified Manufacturer

Ideal Uses

- Wall and Ceiling Linings for Sheds
- Sleep-out Linings
- Bach's & Man Cave Linings
- Lights Commercial Projects

Handling & Application/ Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. At Plymasters, precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important with pine ply (as it is a softwood), where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

