

Rapidline White Oak

Specification Sheet

Economy grade unfinished White Oak veneer B/CC. Specifically for budget conscious projects, great for lining sheds, sleep outs, garages and tiny homes. With a light weight poplar core, Rapidline White Oak is easy to install.

Product Info

| Code | Sheet Size | Thickness | Lay-up | Weight | Grading |
|---------|-------------|-----------|--------|--------|---------|
| J1025-W | 2400 x 1200 | 12mm | 7 Ply | 18kg | B/CC |

Technical Specs

| | |
|-----------|-------------------------------|
| Colour | Light blonde-white oak veneer |
| Glue bond | MR -Phenolic - E1 |
| Origin | Asia |
| Core | Poplar |

Ideal Uses

- Wall and Ceiling Linings for Sheds
- Sleep-out Linings
- Bach's & Man Cave Linings
- Light Commercial Projects

Handling & Application/ Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. At Plymasters, precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important with pine ply (as it is a softwood), where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

