



# Furnier Smoked Larch

## Specification Sheet

This veneer's sophisticated and contemporary look are thanks to its bold, stripy grain pattern. The smoking process adds further depth to the naturally light golden brown colour and its darker brown grain. Smoked Larch is highly recommended for cabinetry, furniture and kitchens. Matching edge tapes are available.

### Specifications

Code	Sheet Size	Thickness	Core	Weight	Grading
V10218-B18SmkL	2500 x 1250	19mm	Birch Ply	37.5kg	AB
V19-MDF-18SmkL	2440 x 1220	19mm	MR-MDF	41.3kg	AB

### Technical Specs

Colour	Golden brown - Dark brown
Texture	Raw - Sanded
Glue bond	Veneer - PVAC D3 (EN204)
Origin	Northern Europe
Certification	PEFC Certified Supplier

### Ideal Uses

- Kitchen cabinetry
- Wall Panelling
- Commercial cabinetry
- Commercial and hospitality furniture

**Handling & Application/** Furnier, despite being a very durable product is still vulnerable to moisture and UV. Consequently it is the users responsibility to ensure the sheets are sealed with a protective coating to give the product the necessary protection from UV moisture and for the desired performance. This is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimise this effect. However, once the panel has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

