



## CLASSIQUE PLYWOOD / SPECIFICATION

**OVERVIEW /** The Classique Plywood range is specifically designed for wall and ceiling lining applications. It is a high-grade interior ply, with a Euro Poplar core and the option of White Oak, Canadian Oak or Euro Birch, Birch-Pre external veneer finishes.

Beautiful and lightweight. this is a decorative interior product that is non-structural.

**USES /** Ceilings / Wall Linings / Feature Walls / Feature Ceilings / Lightweight Cabinetry / Tiny-house interiors

### SPECIFICATIONS /

Code	Sheet Size	Thickness	Colour	Weight	Grading
V2112-B	2440 x 1220	12mm	Euro Birch	16kg	AB Poplar Core
V2112-PRE-B	2440 x 1220	12mm	Euro Birch-Pre	16kg	Clear Finished
V2118-PRE-B	2440 x 1220	18mm	Euro Birch-Pre	23kg	Clear Finished
V2112-W	2440 x 1220	12mm	White Oak	16kg	AB Poplar Core
V2118-W	2440 x 1220	18mm	White Oak	23kg	AB Poplar Core
V2112-C	2440 x 1220	12mm	Canadian Oak	16kg	AB Poplar Core
V2118-C	2440 x 1220	18mm	Canadian Oak	23kg	AB Poplar Core
V2112-PRE-C	2440 x 1220	12mm	Canadian Oak - Pre	16kg	Clear Finished

Colour	Natural timber colourings - European Poplar Core
Durability	Good durability / Interior
Glue bond	E1 - Class 3. Density - 440 - 490Kg/m <sup>3</sup>
Origin	Spain
Prefinished options	UV Clear finished 2S, 30% gloss, low VOC
Environment	FSC C116880 / Plantation Grown / PEFC 14-34-00002

**HANDLING & APPLICATION /** Classique ply is a lighter weight timber than other plywoods, the highly visual surface will harden once a good quality lacquer is applied. Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

