



Vorlac Blonded Birch

Specification Sheet

The Vorlac Plywood is a European Birch plywood Core with a Blonded Birch veneer laid on each Face. These panels have been prefinished in a UV Cured lacquer. No need to head to the paint shop, Vorlac is ready to be installed, saving time and man - hours, while still providing a high - end finish and quality ply.

Product Info

Code	Sheet Size	Thickness	Core	Weight	Grading
V1025-B18B-BL	2500 x 1250	19mm	Birch	37.5kg	AB

Technical Specs

Colour	Blonded Birch
Finish	8-10% 2F Matt Gloss
Glue bond	Veneer - PVAC D3 (EN204) Birch - Exterior Phenolic
Origin	Northern Europe
Certification	FSC & PEFC Certified Supplier

Ideal Uses

- Kitchen cabinetry
- Wall Panelling
- Commercial cabinetry
- Commercial and hospitality furniture

Handling & Application / The Vorlac Range despite being a very durable product is still vulnerable to moisture and UV. Consequently it is the users responsibility to ensure the edges are sealed with a protective coating to give the product the necessary protection from UV moisture and for the desired performance. This is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimise this effect. However, once the panel has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

