

Structural Pine Ply H3.2 Treated

Specification Sheet

Construction H3.2 CCA Ply is treated for high durability in exterior or wet area situations. H3 CCA ply is particularly popular in many roofing and flooring systems as a structural panel.

This Plymasters product manufactured to AS/NZ 2269, which can be used in a variety of situations from residential to commercial and industrial applications.

Product Info

Code	Sheet Size	Thickness	Weight	Treatment	Face Grade
T1010	2400 x 1200	7mm	10.1kg	H3.2	CD
T1015	2400 x 1200	9mm	12.9kg	H3.2	CD
T1020	2400 x 1200	12mm	17.2kg	H3.2	CD
T1025	2400 x 1200	15mm	20.5kg	H3.2	CD
T1035	2400 x 1200	17/ 18mm	25.5kg	H3.2	CD
T1040	2400 x 1200	19mm	23.7kg	H3.2	CD
T1045	2400 x 1200	21mm	30.2kg	H3.2	CD
T1050	2400 x 1200	25mm	36kg	H3.2	CD

Technical Specs

Colour	Pinus Radiata, with light green treatment colouring
Glue Bond	A Bond, Super E-Zero on Request
Origin	NZ
Environmental	Sustainably Grown

Ideal Uses

- Flooring
- Wall Linings
- Roofing
- General Construction

Handling & Application/ Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse, we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

