



# PLYMASTERS

## Plywood & Panels



## HOOP PINE / SPECIFICATION

**OVERVIEW /** Plymasters Hoop Pine ply comes from 100% plantation-grown forests. A light cream colour, with a consistent grain pattern, it is brighter than NZ Pine. This rotary cut softwood, is extremely popular in architectural linings, particularly large ceiling areas. Hoop Pine also has an excellent multi - ply edge detail that suits a wide range of joinery applications. Door straighteners may be required in cabinetry door situations.

**USES /** Specialist Furniture / Wall & Ceiling Linings / Joinery, Kitchen Fit-outs / Feature Panels and both Domestic and Commercial Cabinetry / Limited suitability for free standing doors

### SPECIFICATIONS /

Code	Sheet Size	Thickness	Lay-up	Weight	Grading
J2100-E	2400 x 1200	12mm	9Ply	17.3kg	AC / A Bond
J2108-E	2400 x 1200	18mm	13Ply	25.5kg	AC / A Bond
J2120-E	2400 x 1200	25mm	17Ply	36.2kg	AC / A Bond

Colour	Light cream, Queensland softwood
Texture	Fine Grain - Rotary Cut
Glue bond	A-Bond exterior
Origin	Plantation Source, Queensland, Australia
Certification	FSC 100%, (FSC-C107681)
Emissions	Meets E0 spec of AS/NZS 2271

**HANDLING & APPLICATION /** Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow. Hoop Pine is particularly susceptible to this.

At Plymasters, precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/ cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

