



Builders Grade Pine CD Non-Structural

Specification Sheet

Builders Grade Pine CD UT Non-structural Ply has a variety of uses throughout the construction industry, particularly when structural characteristics are not required, whether that means not bearing weight or in cases where there is no requirement to meet the construction codes of New Zealand. This square edge product offers one side that allows for a certain level of closed and repaired defects, and a reverse side that allows for appearance defects and open defects, conditions that allow it to be used in several applications. Builders Grade Ply is suitable for non-structural packaging, linings, shelving, fit-outs and DIY projects.

Product Info

Code	Sheet Size	Thickness	Lay-up	Weight	Grading
P1045-NS	2400 x 1200	12mm	9Ply	17.2kg	CD
P1075-NS	2400 x 1200	18mm	13Ply	25.5kg	CD

Technical Specs

Colour	Creamy yellow to light brown
Glue Bond	A bond, Super E0
Origin	Chile/ NZ on request
Environment	PEFC

Ideal Uses

- Flooring
- Wall Linings
- Bracing
- General Construction

Handling & Application / Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse, we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

