

Colour Oak Sand Beige

Specification Sheet

Sand Beige Oak Quarter Cut is American White Oak, quarter sawn and laid mismatched. It is then dyed in practical, neutral sand beige, producing consistently-coloured, scratch resistant prefinished panels, which retain the distinctive uniform quarter cut grain. A clear, super-matte lacquer seal finishes the look. Matching edge tape available.

Product Info

Code	Sheet Size	Thickness	Core	Weight	Grading
VC19-MDF-18SdB	2440 x 1220	19mm	MR-MDF	37.5kg	AB

Technical Specs

Colour	Quarter Oak Dyed Sand Beige	
Finish	8-10% Gloss Lacquer	
Glue bond	Veneer - PVAC D3 (EN204)	
Origin	Northern Europe	
Certification	FSC & PEFC Certified Supplier	

Ideal Uses

- Kitchen cabinetry
- Wall Panelling

- Commercial cabinetry
- Commercial and hospitality furniture

Handling & Application/ Coloured Oaks, despite being a very durable product is still vulnerable to moisture and UV. Consequently it is the users responsibility to ensure the sheets are sealed with a protective coating to give the product the necessary protection from UV moisture and for the desired performance. This is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimise this effect. However, once the panel has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

