

# Supalam Panels

# Specification Sheet

Supalam is a hard-wearing carcass plywood which is an excellent alternative to MDF-based panels. This HPL surface provides exceptional durability while a hardwood core provides greater strength. Hard wearing, cost-effective and easy to clean, this product has a light embossed finish. Supalam is moisture resistant.

### **Product Info**

Code	Sheet Size	Thickness	Name	Colour	Weight	Grading
H1995	2440 x 1220	12mm	Embossed Pure White		22.7kg	Carcass Joinery
H1997	2440 x 1220	16mm	Embossed Pure White		27.7kg	Carcass Joinery
H2000	2440 x 1220	18mm	Embossed Pure White		31.5kg	Carcass Joinery
H1997-G	2440 x 1220	16mm	Embossed Grey		27.7kg	Carcass Joinery
H2000-G	2440 x 1220	18mm	Embossed Grey		31.5kg	Carcass Joinery
H1997-B	2440 x 1220	16mm	Embossed Black		27.7kg	Carcass Joinery
H2000-B	2440 x 1220	18mm	Embossed Black		31.5kg	Carcass Joinery
H1997-DG	2440 x 1220	16mm	Embossed Dark Grey		27.7kg	Carcass Joinery
H2000-DG	2440 x 1220	18mm	Embossed Dark Grey		31.5kg	Carcass Joinery

# **Technical Specs**

Colour	White, Black, Grey and Dark Grey
Core	Eucalyptus, Mixed L/Hardwood core, scarf jointed veneers
Glue bond	WBP Phenolic
Origin	China, S.E Asia
Certification	FSC-STD-40 - 004 V21, CE
Environment	Plantation Grown / FSC

#### Ideal Uses

- Kitchen and Laundry Carcass work
- Locker units and partitioning

- Commercial and Wet area Cabinetry carcass
- Vehicle fit-out interiors

Handling & Application/ Supalam is a very cost effective carcass ply. A higher grade panel should be used in a door or "full visual" situation, especially if exposed edge grain is required. It is important to note the this product is a "panel" laminate, and therefore not guaranteed in high wear bench-top situations. Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect the top and edges.