

Colour Oak Velvet Black

Specification Sheet

Velvet Black Oak Quarter Cut is American White Oak, quarter sawn and laid mismatched as a veneer. It is then dyed in dramatic black, producing consistently-coloured, scratch resistant prefinished panels, which retain the distinctive uniform quarter cut grain. A clear, super-matte lacquer seal finishes the look. Matching edge tape available.

Product Info

| Code | Sheet Size | Thickness | Core | Weight | Grading |
|----------------|-------------|-----------|--------|--------|---------|
| VC19-MDF-18VBk | 2440 x 1220 | 19mm | MR-MDF | 37.5kg | AB |

Technical Specs

| Colour | Quarter Oak Dyed Velvet Black |
|---------------|-------------------------------|
| Finish | 8-10% UV Lacquer |
| Glue bond | Veneer - PVAC D3 (EN204) |
| Origin | Northern Europe |
| Certification | FSC & PEFC Certified Supplier |

Ideal Uses

• Kitchen cabinetry

Commercial cabinetry

Wall Panelling

Commercial and hospitality furniture

Handling & Application/ Coloured Oaks, despite being a very durable product is still vulnerable to moisture and UV. Consequently it is the users responsibility to ensure the sheets are sealed with a protective coating to give the product the necessary protection from UV moisture and for the desired performance. This is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimise this effect. However, once the panel has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.